



APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 40 kVA 40000 W

Brand : APC

Product code: E3SUPS40KH

Product name : Easy 3S

APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 40 kVA, Output power: 40000 W. Form factor: Tower, Product colour: White, International Protection (IP) code: IP20. Compliance certificates: RoHS, Certification: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Width: 250 mm, Depth: 900 mm, Height: 770 mm. Package width: 400 mm, Package depth: 1050 mm, Package height: 1015 mm




Features		Design	
UPS topology *	Double-conversion (Online)	Product colour *	White
Output power capacity *	40 kVA	International Protection (IP) code	IP20
Output power *	40000 W	Operational conditions	
Waveform *	Pure sine	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (min) *	304 V	Storage temperature (T-T)	-15 - 40 °C
Input operation voltage (max) *	477 V	Operating relative humidity (H-H)	0 - 95%
Input frequency *	45/65 Hz	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (min)	380 V	Operating altitude	0 - 984.3 m
Output operation voltage (max)	415 V	Non-operating altitude	0 - 14763.6 m
Output frequency	50/60 Hz	Certificates	
Maximum current	73 A	Compliance certificates	RoHS
Number of input phases	3	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Number of output phases	3	Packaging content	
Input power factor	0.99	Management card included	✗
Crest factor	3:1	Quick installation guide	✓
Overload capacity (10 minutes)	125%	Weight & dimensions	
Overload capacity (1 minute)	150%	Width	250 mm
Output voltage Total Harmonic Distortion (THD)	3%	Depth	900 mm
Input current Total Harmonic Distortion (THD)	3%	Height	770 mm
Noise level	63 dB	Weight	70 kg
Ports & interfaces			
SmartSlot	✓		

Ports & interfaces		Packaging data	
SmartConnect port	×	Package width	400 mm
Design		Package depth	1050 mm
Form factor *	Tower	Package height	1015 mm
		Package weight	86 kg
Logistics data			
		Harmonized System (HS) code	85078000
Other features			
		Output voltage	400 V



0731304339571



731304339571

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.