



D-Link DES-1016A network switch Unmanaged Brown

Brand : D-Link
Product code: DES-1016A
Product name : DES-1016A



DES-1016A, Fast Ethernet, SOHO/SMB, Auto MDI/MDIX, IEEE 802.3x, CSMA/CD, 16 x RJ-45, 2.3 W, Brown

D-Link DES-1016A network switch Unmanaged Brown:

CREATE A WIRED NETWORK INSTANTLY
With D-Link DES-1016A and DES-1024A, you can easily expand your network by adding more computers or devices with speeds up to 200 Mbps per port in full duplex mode.

AUTO-SENSING 10/100 PORTS
The DES-1016A and DES-1024A both use auto-sensing 10/100 Mbps ports, allowing a small workgroup to flexibly connect to 10 or 100Mbps devices to create an integrated network. Each port automatically adjusts for straight-through or crossover cables to make the right link.

FLOW CONTROL FOR SECURE TRANSMISSION
802.3x Flow Control on each port minimizes dropped packets when the port’s receiving buffer is full.

Management features		Performance	
Switch type *	Unmanaged	Mean time between failures (MTBF)	840221 h
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	16	Number of power supply units	1
Power connector	DC-in jack	Input voltage	100 - 240 V
		Power consumption (typical)	2.3 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) *	✗
10G support *	✗	Other features	
Full duplex	✓	Dimensions (WxDxH)	280 x 125.8 x 44 mm
Flow control support	✓	Networking features	Fast Ethernet
Auto MDI/MDI-X	✓	Wi-Fi	✗
Data transmission		Power LED	✓
Supported data transfer rates	10/100 Mbps	Connectivity LEDs	✓
Switching capacity *	3.2 Gbit/s	Input frequency	50 - 60 Hz
MAC address table *	8000 entries	Operational conditions	
Store-and-forward	✓	Operating temperature (T-T)	0 - 40 °C
Maximum data transfer rate	0.1 Gbit/s	Storage temperature (T-T)	-10 - 70 °C
Packet buffer memory	2 MB	Operating relative humidity (H-H)	10 - 85%
Security		Storage relative humidity (H-H)	10 - 90%
MAC address filtering	✓	Operating temperature (T-T)	32 - 104 °F
Design		Certificates	
Rack mounting *	✗	Certification	FCC, ICES-003, CE, C-Tick, cUL, LVD
Stackable *	✓		
Product colour	Brown		
LED indicators	Link		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.